

SOLEAL

THE UNIVERSAL WINDOW



Architect: A.D.H.
Photography: DR Technal

IMAGINE WHAT'S NEXT

 TECHNAL



Architect: Manuelle Gautrand
Photography: Vincent Fillon

SOLEAL casement

/ A RANGE OF DIFFERENT SOLUTIONS

AN ALL-IN-ONE DESIGN

The SOLEAL range offers many possibilities for your projects. SOLEAL is available in two main styles, the visible opening window and the minimal opening window, thus accommodating all your stylistic needs. This range is characterised by the number of options available: 1 & 2 leaf windows and balcony doors, integrated or stacked units, casements on sills, with transom or side light, and tilting, turning, projecting and top-hung casements.


Most of these options are available in two types of module:

- 55 mm with a 20 mm thermal break
- 65 mm with a 30 mm thermal break.

The evolutionary nature of this range means that it will be able to cope with the increasingly demanding regulatory requirements of the future. The balcony doors are also available with disabled access thresholds. The installation and finishing options are the same for both SOLEAL doors and sliding systems.

A NEW GENERATION OF WINDOWS

The SOLEAL range offers exceptional thermal and acoustic performance, and weather resistance - properties which come as standard with the new generation of TECHNAL windows. As a result, SOLEAL not only meets current regulatory demands but anticipates future requirements with its high performance.




Architect: W Architectures
Photography: DR Technal


MINIMAL



MINIMAL




The flashing ensures the seamless integration of the opening frame and the fixed and opening sections appear as one. The fine, minimalist lines are reminiscent of the steel frame construction used for commercial buildings.




Available in the 55 mm and 65 mm version



EQUILIBRE




Consistent external appearance for the whole assembly. A harmonious balance between the mullions and transoms. Composite assemblies for large sizes whilst still minimising the external visual impact with a 66-mm aluminium frame.




Available in the 55 mm version



CLIP-ON TRIM



The clip-on trim subtly borders the opening frame, giving it a contemporary feel.




Available in the 55 mm and 65 mm version


VISIBLE



VISIBLE



The visual impact of the opening and outer frames has been carefully balanced resulting in an assembly purveying opulence and high quality.



Available in the 55 mm and 65 mm version

SOLEAL

/ THE UNIVERSAL
WINDOW

SOLEAL MINIMAL
EN 55 MM



SOLEAL VISIBLE
EN 65 MM



KEY FEATURES AND INNOVATIONS

DESIGN

- Several versions are available to meet all your projects' requirements:
 - Minimal: a minimalist opening frame with fine and subtle lines
 - Equilibre: a minimalist version which emphasises the symmetry and finesse of the assemblies
 - A minimalist opening frame with "clip-on trim" creating a contemporary feel
 - A visible opening assembly purveying opulence and high quality
 - Concealed drainage for discrete water removal from all configurations of opening as well as fixed frames
 - Flashings available in different shapes and styles

MULTIPLES CONFIGURATIONS

- Fixed casement
- 1 and 2 leaf
- Integrated or stacked composite assemblies with transom or side lights
- Projecting top-hung casement

THERMAL, WEATHER RESISTANCE AND ACOUSTIC PERFORMANCE

- SOLEAL casement frames meet the demands of regulatory changes: RT2012, permeability criteria for Low Energy Consumption Buildings and acoustic attenuation requirements in urban areas

CLOSURE SYSTEMS AND SECURITY

- Various combinations are available up to 6-point with or without key locking systems
- Handles centred on the central mullions of 2-leaf casements reduced to 66 mm (minimal opening frame) and 116 mm (visible opening frame) are available as an option
- The Technal-exclusive handles are available for all configurations and ensure style consistency regardless of the type of opening system and can be adapted for use on doors and sliding systems
- Windows subjected to forced entry delay tests achieving a score of RC2 in accordance with the EN-1627-30 standard.

ACCESSIBILITY

- System adapted for easy access for all available configurations

INNOVATION

- 7 patents for innovative window vision
- 3 patents pending for aesthetic ideals

SOLEAL / MADE-TO-MEASURE DESIGN

PURETY, FINESSE AND SUBTLETY




Minimal version



Clip-On Trim
Minimal version




Visible version



Concealed drainage



Subtle edges




Concealed hardwares

A WIDE RANGE OF CLOSURE SYSTEMS




Stainless steel
handle



Exclusive Technal-designed
handle




Exclusive Technal-designed
handle with lock



Classic handle



Closure systems
operated via 2-way
espagnolette locking
and drive



Architects: Ateliers Jean NOUVEL / François Fontès Architecture
Photography: Luc Boegly



SOLEAL / FOR DISABLED USERS

The disabled access thresholds used on SOLEAL balcony doors meet the requirements of the French regulations for door and balcony door access whilst ensuring optimum weather tightness



Disabled access threshold with thermal break

SECURITY

- Windows can be fitted with 2 to 6 point locks depending on the desired level of security.
- Windows have been subjected to forced entry delay tests achieving a score of RC2 in accordance with the EN-1627-30 standard.



Top point



Mid-point between the handle and mechanism



Bottom of opening frame



Bottom of outer frame

SOLEAL CASEMENT FRAME 55

/ ADAPTABILITY AND DIVERSITY

WIDE RANGE

Several models are offered to meet all stylistic requirements:
• "Contemporary" for residential or commercial architectural projects
• "Classic" for projects involving the general public
• "Traditional" to provide an exact replacement for the original joinery used on traditional buildings
• The installation and covering conditions are the same for both SOLEAL doors and sliding systems

MULTIPLE CONFIGURATIONS

- Fixed casement
- 1 and 2 leaf
- Integrated or stacked composite assemblies with transom or side lights
- Projecting and top-hung casement

2 VERSIONS OF OPENING FRAMES

- Minimal and Clip-on trim versions opening frame with glazing infills up to 32 mm
- Visible opening frame with glazing infills up to 42 mm
- The fixed sections shared by both types of opening frames can accommodate glazing up to 42 mm

THERMAL, WEATHER RESISTANCE AND ACOUSTIC PERFORMANCE

- Optimised thermal loss values U_w up to $1.2 \text{ W/m}^2 \cdot ^\circ\text{K}$, $S_w = 0.41$ and $LTw = 0.54$ with triple glazing ($U_g = 0.6 + \text{warm edge}$)
- Very low air permeability meeting 2012 thermal regulations Q4 up to $0.058 \text{ m}^3/(\text{h.m}^2)$
- Very good thermal performance: up to 40 dB [RA, Tr] of acoustic attenuation. Test on window with 44.1/20/12 glazing

CONTEMPORARY MODEL




EXTERNAL VIEW

CLASSIC MODEL



TRADITIONAL MODEL



INTERNAL VIEW



For architectural projects



For residential projects




For traditional buildings

| | VISIBLE | CLIP-ON TRIM | MINIMAL | EQUILIBRE |
|--------------|---------|--------------|---------|-----------|
| Contemporary | x | x | x | x |
| Classic | x | x | x | |
| Traditional | x | x | x | |



Architect: ANMA


Photography: Stéphane Chalmeau





CROSS-SECTIONS

SOLEAL 55 MINIMAL

1 AND 2 LEAF WINDOW AND BALCONY DOOR




CENTRED HANDLE OPTION




SOLEAL 55 MINIMAL
EQUILIBRE VERSION

- The “Equilibre” version offers symmetry between the external appearance of all configurations of 66 mm assemblies.
- The integration of minimal opening frames is characterised by fine and simple lines.
- The various internal reinforcement solutions, 95 or 120 mm, vertical or horizontal, means that the facades can incorporate floor to ceiling designs (3 m).
- The drainage systems, which are fully integrated into the transoms, provide a smooth and flat external appearance.




1 Fixed transom on the 66 mm with concealed drainage


2 Opening frame transom



3 Flat external appearance of the mullion on the 66 mm with aluminium reinforcement



Composite frame with double leaf open-in on fixed sill with 4 lateral sections




4 Subtlety of the opening vent's central mullion
2 leaves = 66 mm


CROSS-SECTIONS

SOLEAL 55 MINIMAL
CLIP-ON TRIM VERSION

1 AND 2 LEAF WINDOW AND BALCONY DOOR





INTEGRATION INTO GEODE CURTAIN WALLING




SOLEAL 55 VISIBLE

1 AND 2 LEAF WINDOW AND BALCONY DOOR



CENTRED HANDLE OPTION





Architect: Manuelle Gautier
Photography: Vincent Filton

SOLEAL CASEMENT FRAME 65

/ ADVANCED PERFORMANCE

THERMAL AND WEATHER RESISTANCE PERFORMANCE

- Optimised thermal loss values up to $0.9 \text{ W}/^{\circ}\text{K}$, $\text{Sw} = 0.41$ and $\text{LTw} = 0.54$ with triple glazing ($\text{Ug} = 0.5 + \text{warm edge}$)
- Very low air permeability meeting 2012 thermal regulations Q4 up to $0.02 \text{ m}^3/(\text{h.m}^2)$

ACOUSTIC PERFORMANCE SUITED TO URBAN ENVIRONMENTS

- Very good sound-proofing: up to 43 dB (RA, Tr) of acoustic attenuation
- Test on window with 88.1/-20/-66.2 sound-proof glazing

2 VERSIONS OF OPENING FRAMES

- To meet all market needs, many of the configurations of the SOLEAL 65 range are available in opening and open-out versions
- Minimal open-in frame glazing infill up to 42 mm
- Visible opening frame (open-in and open-out) glazing infill up to 52 mm
- The fixed sections shared by both types of opening frames can accommodate glazing up to 52 mm

CONCEALED HARDWARES ON VISIBLE OPENING FRAME

- Available with 110° opening and maximum weight: 160 kg
- Offers a variety of frames: 1 leaf, 2 leaves, French, tilt & turn opening frames

MULTIPLE CONFIGURATIONS

- Fixed casement
- 1 and 2 leaf
- Integrated or stacked composite assemblies with transom or side lights


SPECIAL OPENINGS

- Top-hung casement
- Projecting casement
- Parallel casement
- Horizontal and vertical pivot casement
- Turn/slide casement


CROSS-SECTIONS

SOLEAL 65 MINIMAL
OPEN-IN

1 AND 2 LEAF WINDOW AND BALCONY DOOR




INTEGRATION INTO GEODE CURTAIN WALLING
OPEN-IN AND OPEN-OUT





SOLEAL 65 VISIBLE
OPEN-IN

1 AND 2 LEAF WINDOW AND BALCONY DOOR




CONCEALED HARDWARES






SOLEAL 65 VISIBLE
OPEN-OUT


1 AND 2 LEAF WINDOW AND BALCONY DOOR



32




36




SOLEAL 65 VISIBLE



TIILT/TURN CASEMENT



2-LEAF BALCONY DOOR WITH DISABLED
ACCESS THRESHOLD
OPEN-IN



TOP-HUNG CASEMENT
OPEN-OUT





CONFIGURATIONS

All configurations feature concealed drainage.
All balcony door configurations are available with
disabled access thresholds

EXTERNAL VIEW DIAGRAMS


OPEN-IN

* 55 and 65 mm version



SPECIAL OPENINGS


** 65 mm version



OPEN-OUT

* 55 and 65 mm version


** 65 mm version




SOLEAL CASEMENT

/ INSTALLATION CASES (SAME FOR 55 AND 65 MM)

INSTALLATION INTO EXTERNAL CLADDING




INTERNAL INSTALLATION



SOLEAL CASEMENT FRAME

/ INSTALLATION CASES (SAME FOR 55 AND 65 MM)

INSTALLATION FOR RENOVATION



Architects: Taillandier Architectes Associés
Photography: DR Technal

SOLEAL CASEMENT FRAME 55

/ PERFORMANCE

Whether for residential or commercial buildings, the RT 2012 aims to limit the maximum energy consumption of new buildings.

There are no minimum requirements in terms of frames but Technal has been assisting architects with these new demands.

Therefore, SOLEAL windows contribute to maintaining the permeability of the building's outer shell thanks to very good Q4 ratings.

| WEATHER TIGHTNESS A.E.V. (Air, Water, Wind) | | | | | | |
|---|-----------------|---|----|----|------|------|
| Configurations | Size W x H in m | A | W | Wi | Q4 | Q100 |
| Soleal Minimal | | | | | | |
| Window | | | | | | |
| 1 leaf Turn/tilt | 1,6 x 1,8 | 4 | 9A | C3 | 0 | 0 |
| Balcony door | | | | | | |
| 1 leaf | 1,26 x 2,28 | 4 | 9A | C3 | 0,5 | 1,27 |
| 2 leaves with disabled access threshold | 1,4 x 2,25 | 4 | 8A | C3 | 0,12 | 0,36 |
| Soleal Visible | | | | | | |
| Window | | | | | | |
| 1 leaf Turn/tilt | 1,4 x 1,6 | 4 | 9A | C3 | 0 | 0 |
| Balcony door | | | | | | |
| 1 leaf split-hinge 3 blades | 1,2 x 2,25 | 4 | 9A | C3 | 0 | 0 |

| ACOUSTIC PERFORMANCE | | | | | | | | | | |
|----------------------------|---------------|-----------------|----------------|----|-------|----------------|----|-------|--|--|
| Configurations | Designation | Size W x H in m | Glazing | | | Window | | | | |
| | | | Rw (C; Ctr) | Ra | Ra,Tr | Rw (C; Ctr) | Ra | Ra,Tr | | |
| SOLEAL Minimal and Visible | | | | | | | | | | |
| Window | | | | | | | | | | |
| 1-leaf MOF turn/tilt | 6[16] 4 | 1,45 x 1,48 | 34 | 33 | 29 | 34 | 33 | 31 | | |
| 1-leaf MOF turn/tilt | 64-1SI[12] 10 | 1,45 x 1,48 | 42 | 40 | 37 | 42 | 41 | 38 | | |
| 1-leaf MOF turn/tilt | 6[16] 4 | 1,45 x 1,48 | 34 | 33 | 29 | 35 | 34 | 31 | | |
| 1-leaf MOF turn/tilt | 44-1SI[20] 12 | 1,45 x 1,48 | 46 | 44 | 40 | 43 | 43 | 40 | | |
| 1-leaf MOF turn/tilt | 12[12]8 | 1,23 x 1,48 | 38 | 37 | 35 | 37 | 36 | 35 | | |
| Balcony door | | | | | | | | | | |
| 2- leaf VOF | 6[16] 4 | 1,45 x 2,18 | 34 | 33 | 29 | 36 | 35 | 32 | | |

According to EN 14351-1 for windows, this performance data is valid for:

- Rw + Ctr glazing [for the Ra,Tr rating] equal to or greater than the values of the tested glazing- corrections
- 1 dB for leaf surface area of + 50% to + 100% / - 2 dB for + 100% to + 150% / - 3 dB for + 150% to + 200%

MOF = Minimal Opening Frame

VOF = Visible Opening Frame

| WEATHER TIGHTNESS (Air, Water, Wind) | Equivalence | |
|--|-------------|-------|
| | Q4 | Q100* |
| Individual housing unit m ³ (h.m ²) | 0,6 | 5,1 |
| Collective housing unit m ³ (h.m ²) | 1 | 8,5 |

*Q100 represents the casement leak at 100 pascals. For Low Energy Consumption Buildings, the Q100 must not exceed 5.1 for individual housing units and 8.5 for collective housing units (m³/(h.m²)).

SOLEAL CASEMENT FRAME 55

/ PERFORMANCE

| THERMAL PERFORMANCE | | | | | | | |
|--|-----------------|--------------------------|------------------------------|------------------------------|------------------------------|--|--|
| | Size W x H in m | | With Ug = 1,1 + Warm edge | With Ug = 1,0 + Warm edge | With Ug = 0,8 + Warm edge | | |
| Soleal Minimal | | | | | | | |
| Window | | | | | | | |
| 1 leaf | 1,25 x 1,48 | Uw (W/m ² .K) | 1,5 | 1,5 | 1,3 | | |
| | | Sw | 0,52 | 0,42 | 0,42 | | |
| | | TLw | 0,64 | 0,57 | 0,57 | | |
| 2 leaves | 1,53 x 1,48 | Uw (W/m ² .K) | 1,6 | 1,6 | 1,4 | | |
| | | Sw | 0,50 | 0,40 | 0,40 | | |
| | | TLw | 0,61 | 0,54 | 0,54 | | |
| Balcony door | | | | | | | |
| 1 leaf | 1,25 x 2,18 | Uw (W/m ² .K) | 1,5 | 1,4 | 1,2 | | |
| | | Sw | 0,54 | 0,43 | 0,43 | | |
| | | TLw | 0,67 | 0,59 | 0,59 | | |
| 2 leaves | 1,53 x 2,18 | Uw (W/m ² .K) | 1,6 | 1,5 | 1,3 | | |
| | | Sw | 0,51 | 0,41 | 0,41 | | |
| | | TLw | 0,63 | 0,56 | 0,56 | | |
| Soleal Minimal - Clip-on trim | | | | | | | |
| Window | | | | | | | |
| 1 leaf | 1,25 x 1,48 | Uw (W/m ² .K) | 1,6 | 1,5 | 1,3 | | |
| | | Sw | 0,52 | 0,41 | 0,41 | | |
| | | TLw | 0,65 | 0,57 | 0,57 | | |
| 2 leaves | 1,53 x 1,48 | Uw (W/m ² .K) | 1,7 | 1,6 | 1,5 | | |
| | | Sw | 0,49 | 0,39 | 0,39 | | |
| | | TLw | 0,61 | 0,54 | 0,54 | | |
| Balcony door | | | | | | | |
| 1 leaf | 1,25 x 1,48 | Uw (W/m ² .K) | 1,5 | 1,4 | 1,3 | | |
| | | Sw | 0,53 | 0,42 | 0,42 | | |
| | | TLw | 0,67 | 0,59 | 0,59 | | |
| 2 leaves | 1,53 x 1,48 | Uw (W/m ² .K) | 1,6 | 1,5 | 1,4 | | |
| | | Sw | 0,51 | 0,41 | 0,41 | | |
| | | TLw | 0,63 | 0,56 | 0,56 | | |
| Balcony door with disabled access threshold | | | | | | | |
| 1 leaf | 1,25 x 2,18 | Uw (W/m ² .K) | 1,5 | 1,5 | 1,3 | | |
| | | Sw | 0,54 | 0,43 | 0,43 | | |
| | | TLw | 0,67 | 0,6 | 0,6 | | |
| 2 leaves | 1,53 x 2,18 | Uw (W/m ² .K) | 1,6 | 1,6 | 1,4 | | |
| | | Sw | 0,51 | 0,41 | 0,41 | | |
| | | TLw | 0,63 | 0,57 | 0,57 | | |

Uw: Frame thermal loss / Sw: Solar factor / LTW: Light transmission

| THERMAL PERFORMANCE* | | | | | | |
|---------------------------------------|-----------------|--------------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| | Size W x H in m | | With Ug = 1,1 + Warm edge | With Ug = 1,0 + Warm edge | With Ug = 0,8 + Warm edge | With Ug = 0,6 + Warm edge |
| Soleal Visible - Open-in | | | | | | |
| Window | | | | | | |
| 1 leaf | 1,25 x 1,48 | Uw (W/m ² .K) | 1,6 | 1,5 | 1,4 | 1,2 |
| | | Sw | 0,49 | 0,39 | 0,39 | 0,39 |
| | | TLw | 0,61 | 0,54 | 0,54 | 0,54 |
| 2 leaves | 1,53 x 1,48 | Uw (W/m ² .K) | 1,7 | 1,6 | 1,4 | 1,3 |
| | | Sw | 0,46 | 0,37 | 0,37 | 0,37 |
| | | TLw | 0,56 | 0,5 | 0,5 | 0,5 |
| Balcony door | | | | | | |
| 1 leaf | 1,25 x 2,18 | Uw (W/m ² .K) | 1,5 | 1,4 | 1,3 | 1,1 |
| | | Sw | 0,51 | 0,43 | 0,43 | 0,43 |
| | | TLw | 0,63 | 0,56 | 0,56 | 0,56 |
| 2 leaves | 1,53 x 2,18 | Uw (W/m ² .K) | 1,6 | 1,5 | 1,4 | 1,2 |
| | | Sw | 0,48 | 0,4 | 0,4 | 0,4 |
| | | TLw | 0,58 | 0,52 | 0,52 | 0,52 |
| Soleal Visible - Open-out | | | | | | |
| Top hung window | 1,53 x 1,48 | Uw (W/m ² .K) | 1,7 | 1,6 | 1,5 | 1,3 |
| | | Sw | 0,46 | 0,37 | 0,36 | 0,36 |
| | | TLw | 0,56 | 0,5 | 0,5 | 0,5 |
| Projection window with central gasket | 1,53 x 1,48 | Uw (W/m ² .K) | 1,5 | 1,5 | 1,3 | 1,2 |
| | | Sw | 0,46 | 0,36 | 0,36 | 0,36 |
| | | TLw | 0,56 | 0,5 | 0,5 | 0,5 |

* Thermal performance data obtained with addition insulation at the bottom of the glazing rebate

SOLEAL CASEMENT FRAME 65

/ PERFORMANCE

| WEATHER TIGHTNESS A.E.V. (AIR, WATER, WIND) | | | | | |
|--|-----------------|----------------|-------------------|-------|------|
| Frame under ITT (Initial Type Test) | | | | | |
| Configurations | Size W x H in m | | Report n° | Q4 | Q100 |
| | H x W | Classification | | | |
| Special Openings | | | | | |
| Tilting (visible pivot) | 1,7 x 2 | A3 E8A VC4 | 404/12/276-4 FCBA | 0,41 | 3,54 |
| Turning (concealed pivot) | 2,2 x 1,8 | A4 E6A VC4 | 404/12/413-5 FCBA | 0,08 | 0,72 |
| Visible Open-in Frame | | | | | |
| Window | | | | | |
| 1 leaf Tilt/Turn | 1,6 x 1,2 | A4 E1050 VC4 | 404/12/111-1 FCBA | 0,06 | 0,52 |
| 1 leaf Tilt/Turn | 1,6 x 1,2 | A4 E1050 VC5 | 404/11/231-2 FCBA | 0,06 | 0,53 |
| Balcony door | | | | | |
| 2-leaf balcony doors | 2,25 x 1,6 | A4 E9A VC2 | 404/11/231-1 FCBA | 0,28 | 2,4 |
| 1-leaf balcony door with side light | 2,25 x 2 | A4 E9A VB3 | 404/11/461-3 FCBA | 0,08 | 0,65 |
| Minimal Open-in Frame | | | | | |
| 1-Leaf Tilt/Turn Window | 1,6 x 1,2 | A4 E750 VC4 | 404/12/111-2 FCBA | 0,03 | 0,28 |
| 1-leaf balcony door with side light | 2,25 x 2 | A4 E9A VB3 | 404/12/461-1 FCBA | 0,02 | 0,15 |
| Visible Open-out Frame | | | | | |
| Top-hung assembly (opening frame's dimensions) | 1,5 x 1,4 | A4 E1050 VC4 | 404/12/276-3 FCBA | 0,02 | 0,19 |
| Projection | 1,8 x 1,6 | A3 E1050 VC4 | 404/12/276-1 FCBA | 0,07 | 0,58 |
| Visible opening - Concealed hardwares | | | | | |
| 1-Leaf Tilt/Turn Window | 1,8 x 1,3 | A4 E1200 VC4 | 404/14/29-1 FCBA | 0,063 | 0,54 |
| 1-leaf balcony door with side light | 2,5 x 1,4 | A4 E1200 VC4 | 404/14/29-3 FCBA | 0,015 | 0,13 |

Uw: Frame thermal loss / Sw: Solar factor / LTw: Light transmission

| ACOUSTIC PERFORMANCE | | | | | | | |
|--------------------------------|----------------|-------------|---------------------------|----|-------|--------------------|----|
| Frame size W x H (1480 x 1230) | | | | | | | |
| Configurations | Glazing | Seal AS0180 | Glazing performance alone | | | Window performance | |
| | | | RW [C; Ctr] | RA | RA,tr | RW [C; Ctr] | RA |
| Soleal Visible | | | | | | | |
| 1-leaf turn/tilt VOF | 6-16-10 | | 37 | 36 | 34 | 38 [-2;-3] | 36 |
| 1-leaf turn/tilt VOF | 44.1 sil-16-12 | x | 46 | 44 | 40 | 44 [-2;-5] | 42 |
| Turn/tilt VOF | 88.1-20-66.2 | x | 54 | 53 | 49 | 46 [-1;-3] | 45 |
| Soleal Minimal | | | | | | | |
| 1-leaf turn/tilt MOF | 6-16-10 | | 37 | 36 | 34 | 37 [-1;-3] | 36 |

MOF = Minimal Opening Frame / VOF = Visible Opening Frame

| THERMAL PERFORMANCE | | | | | | |
|------------------------|-----------------|--|---------------------------|---------------------------|---------------------------|---------------------------|
| Soleal Visible | | | | | | |
| Open-in configurations | Size W x H in m | | With Ug = 1,1 + Warm edge | With Ug = 1,0 + Warm edge | With Ug = 0,8 + Warm edge | With Ug = 0,6 + Warm edge |
| | | | Glazing 24 mm | Glazing 24 mm | Glazing 32 mm | Glazing 42 mm |
| | | | SW-V | SW-V | SW-V | Glazing 48 mm |

| Window | | | | | | |
|----------|-------------|-------------|------|------|------|------|
| 1 leaf | 1,25 x 1,48 | Uw (W/m².K) | 1,4 | 1,3 | 1,1 | 1,0 |
| | | Sw | 0,48 | 0,39 | 0,41 | 0,41 |
| | | TLw | 0,61 | 0,54 | 0,54 | 0,54 |
| 2 leaves | 1,53 x 1,48 | Uw (W/m².K) | 1,5 | 1,4 | 1,2 | 1,1 |
| | | Sw | 0,45 | 0,36 | 0,38 | 0,38 |
| | | TLw | 0,56 | 0,50 | 0,50 | 0,50 |

| Balcony door | | | | | | |
|--------------|-------------|-------------|------|------|------|------|
| 1 leaf | 1,25 x 2,18 | Uw (W/m².K) | 1,4 | 1,3 | 1,1 | 0,9 |
| | | Sw | 0,50 | 0,40 | 0,42 | 0,42 |
| | | TLw | 0,63 | 0,56 | 0,56 | 0,56 |
| 2 leaves | 1,53 x 2,18 | Uw (W/m².K) | 1,4 | 1,4 | 1,2 | 1,0 |
| | | Sw | 0,47 | 0,37 | 0,39 | 0,39 |
| | | TLw | 0,59 | 0,52 | 0,52 | 0,52 |

| Special Opening Configurations | | | | | | |
|--------------------------------|-------------|-------------|------|------|------|------|
| Tilting/turning | 1,53 x 1,48 | Uw (W/m².K) | 1,7 | 1,6 | 1,4 | 1,3 |
| | | Sw | 0,42 | 0,34 | 0,35 | 0,35 |
| | | TLw | 0,5 | 0,45 | 0,45 | 0,45 |

| THERMAL PERFORMANCE | | | | | | |
|--------------------------------------|-----------------|--|---------------------------|---------------------------|---------------------------|---------------------------|
| Soleal Visible - Concealed hardwares | | | | | | |
| Open-in configurations | Size W x H in m | | With Ug = 1,1 + Warm edge | With Ug = 1,0 + Warm edge | With Ug = 0,8 + Warm edge | With Ug = 0,6 + Warm edge |
| | | | Glazing 24 mm | Glazing 24 mm | Glazing 32 mm | Glazing 42 mm |
| | | | SW-V | SW-V | SW-V | Glazing 48 mm |

| Window | | | | | | |
|----------|-------------|-------------|------|------|------|------|
| 1 leaf | 1,25 x 1,48 | Uw (W/m².K) | 1,5 | 1,4 | 1,4 | 1,1 |
| | | Sw | 0,47 | 0,37 | 0,39 | 0,39 |
| | | TLw | 0,58 | 0,52 | 0,52 | 0,52 |
| 2 leaves | 1,53 x 1,48 | Uw (W/m².K) | 1,6 | 1,5 | 1,5 | 1,2 |
| | | Sw | 0,43 | 0,34 | 0,36 | 0,36 |
| | | TLw | 0,53 | 0,47 | 0,47 | 0,47 |

| Balcony door | | | | | | |
|--------------|-------------|-------------|------|------|------|------|
| 1 leaf | 1,25 x 2,18 | Uw (W/m².K) | 1,5 | 1,3 | 1,2 | 1,0 |
| | | Sw | 0,49 | 0,39 | 0,41 | 0,41 |
| | | TLw | 0,61 | 0,54 | 0,54 | 0,54 |
| 2 leaves | 1,53 x 2,18 | Uw (W/m².K) | 1,4 | 1,4 | 1,3 | 1,1 |
| | | Sw | 0,45 | 0,36 | 0,38 | 0,38 |
| | | TLw | 0,56 | 0,49 | 0,49 | 0,49 |

| THERMAL PERFORMANCE | | | | | | |
|------------------------|-----------------|--|---------------------------|---------------------------|---------------------------|---------------------------|
| Soleal Minimal | | | | | | |
| Open-in configurations | Size W x H in m | | With Ug = 1,1 + Warm edge | With Ug = 1,0 + Warm edge | With Ug = 0,8 + Warm edge | With Ug = 0,6 + Warm edge |
| | | | Glazing 26 mm | Glazing 26 mm | Glazing 32 mm | Glazing 42 mm |
| | | | SW-V | SW-V | SW-V | SW-V |

| Window | | | | | | |
|----------|-------------|-------------|------|------|------|------|
| 1 leaf | 1,25 x 1,48 | Uw (W/m².K) | 1,4 | 1,4 | 1,2 | 1,0 |
| | | Sw | 0,5 | 0,4 | 0,43 | 0,43 |
| | | TLw | 0,64 | 0,56 | 0,57 | 0,57 |
| 2 leaves | 1,53 x 1,48 | Uw (W/m².K) | 1,5 | 1,4 | 1,2 | 1,1 |
| | | Sw | 0,47 | 0,38 | 0,41 | 0,41 |
| | | TLw | 0,6 | 0,54 | 0,54 | 0,54 |

| Balcony door | | | | | | |
|--------------|-------------|-------------|------|------|------|------|
| 1 leaf | 1,25 x 2,18 | Uw (W/m².K) | 1,4 | 1,3 | 1,1 | 1,0 |
| | | Sw | 0,51 | 0,41 | 0,45 | 0,45 |
| | | TLw | 0,66 | 0,58 | 0,59 | 0,59 |
| 2 leaves | 1,53 x 2,18 | Uw (W/m².K) | 1,5 | 1,4 | 1,2 | 1,1 |
| | | Sw | 0,49 | 0,39 | 0,42 | 0,42 |
| | | TLw | 0,62 | 0,55 | 0,56 | 0,56 |

| Balcony door with threshold | | | | | | |
|-----------------------------|-------------|-------------|------|------|------|------|
| 1 leaf | 1,25 x 2,18 | Uw (W/m².K) | 1,4 | 1,4 | 1,2 | 1,0 |
| | | Sw | 0,51 | 0,41 | 0,45 | 0,45 |
| | | TLw | 0,66 | 0,58 | 0,59 | 0,59 |
| 2 leaves | 1,53 x 2,18 | Uw (W/m².K) | 1,5 | 1,4 | 1,2 | 1,1 |
| | | Sw</td | | | | |




Architect: A.D.H.
Photography: DR Technal

EPD (ENVIRONMENTAL PRODUCT DECLARATION)

| Life-cycle indicators | Unit per window | Results |
|---|-----------------------------|------------|
| Non-renewable primary energy | (MJ) | 1948 |
| Renewable primary energy | (MJ) | 129,5 |
| Water consumption | (kg) | 1819 |
| Reduction in abiotic resources | (kg Sb equiv.) | 1,009 |
| Global warming potential | (kg CO ₂ equiv.) | 200,6 |
| Potential for ozone layer depletion | (kg R11 equiv.) | 3,902E-005 |
| Acidification potential | (kg SO ₂ equiv.) | 0,7912 |
| Eutrophication potential | (kg PO ₄ equiv.) | 0,07797 |
| Potential for photochemical ozone formation | (kg ethene equiv.) | 0,09789 |
| Non-hazardous waste | (kg) | 6,853 |
| Hazardous waste | (kg) | 4,256 |

The indicators are based on average representative data for aluminium production in the European Union and generic data for a standard unit of glazing and standard seals.



Horizontal cross-section of the tested system

MATERIALS AND COMPONENTS


As with all Technal systems, only the best materials and parts are used to minimise maintenance and ensure long-term performance.

- The aluminium profiles are extruded from alloys 6060 Building compliant with EN 12020, EN 573-3, EN 515 and EN 775-1 to 9.
- Fittings are cast from EN 12844 compliant Zamak 5.
- All seals are EPDM or TPE (Thermoplastic elastomer).
- The polyamide thermal breaks are extruded from pA6-6 (0.25 FV).
- Screws are made from stainless steel.

FINISHES AND COLOURS

A large range of finishes and colours are available to meet individual project requirements, enhancing existing buildings and offering architects and designers greater design freedom:

- Natural anodised in accordance with EN 23731: 2001.
- Polyester coating finishes in a wide range of colours in accordance with "QUALICOAT" instructions.
- SOLEAL is also available in lacquered finishes with exclusive Technal colours for a stylish and contemporary look.



IMAGINE WHAT'S NEXT

270, rue Léon-Joulin
BP 63709 - 31037 Toulouse cedex 1
FRANCE - www.technal.com

