

SAPA DOOR 2086/2086 SX

HIGH INSULATED DOOR WITH HIGH WEATHER TIGHTNESS

sapa:

By  Hydro

Sapa Door 2086 and 2086 SX


Door 2086 has 86 mm deep profiles, basic insulation level with 42 mm of glass fibre reinforced polyamide strips. For optimum energy performance, choose Door 2086 SX with Sapa Thermo N9 insulating strips in profiles.

System can be specified with choice of three seal performance levels: Standard, Plus and Extreme.


Door leaf profiles are available for narrow and modular locks. Rebate for glass and infill panel 20–56 (64) mm. The outer glazing bead is integrated in the door profile for asymmetrically installed glazing units. These doors can easily be combined with our Facade Systems 4150, 5050 SG and Glazed Elements 3086.


2086 is a highly insulated door. 2086 SX also has Sapa Thermo N9 insulating strips.

The door system can be specified with choice of three seal performance levels.




Door 2086 design example







Sapa Door 2086





Sapa Door 2086 SX

Sapa Door Systems	2086 and 2086 SX		
	Standard	Plus	Extreme
System specification	Standard	Plus	Extreme
Single door	▪	▪	▪
Double doors	▪	▪	
Lock type	Single-point	Single-point	Three-point
Door sill options	6	3	2
Universal hinge	▪	▪	▪
Butt hinge	▪		
Concealed hinge	▪	▪	▪
Door leaf size max., mm	1350x3000	1350x2500	1350x2500
Glass thickness max., mm	56 (64)	56 (64)	56 (64)
Weight max., kg	200	200	200
Airtightness, class according to EN 12207	n/a	2	4
Watertightness classification according to EN 12208	n/a	4A	9A
Wind load classification according to EN 12210	n/a	C2	C3
Repeated opening/closing, classification according to EN 12400	6	6	6
Design choice	Narrow or modular profiles.		
Child safety, anti-finger trap device	Rubber profile/ membrane	Membrane	Membrane
Maintenance	Replaceable rebate section on frame side.		







1 - Door with narrow profile. Illustration shows Door 2086 SX with Sapa Thermo N9 insulating strips in profiles




6 - Double doors, narrow profile




1 - Door with modular profile




10 - Reinforced rebate section




1 - Door 2086 standard with anti-finger trap device, narrow profile




7 - Door with side light. Narrow profile with replaceable rebate section




1 - Door 2086, Plus and Extreme, with anti-finger trap device, narrow profile




10 - Door with narrow profile and E-frame for integrated electronics




4 - Top edge of door with frame




4 - Top edge of door with profile for automated swing door




8 - Top edge of door with top light




8 - Top edge of door with top light and profile for automated swing door




5 - Glazing bars








5 - Glazing bars





5 - Glazing bars




3 - Specification: Door 2086



3 - Specification: Door 2086 SX Plus




Specification: Door 2086 SX Extreme









Typical U-values Sapa Door System 2086

U-values glass (U_g) in W/m^2K		Fully glazed single door without glazing bars			Glazed single door with glazing bars			Fully glazed double door without glazing bars			Glazed double door with glazing bars		
		0.5	0.6	0.7	0.5	0.6	0.7	0.5	0.6	0.7	0.5	0.6	0.7
B	H	U-values door (U_d) in W/m^2K											
1000	2200	1.1	1.2	1.2	1.2	1.2	1.3						
1200	2200	1.0	1.1	1.2	1.1	1.2	1.2						
1600	2200							1.1	1.2	1.2	1.2	1.2	1.3
2000	2200							1.0	1.1	1.2	1.1	1.1	1.2
2400	2200							1.0	1.0	1.1	1.0	1.1	1.2

Typical U-values Sapa Door System 2086 SX

1000	2200	0.9	1.0	1.1	1.0	1.0	1.1						
1200	2200	0.9	1.0	1.0	0.9	1.0	1.1						
1600	2200							0.9	1.0	1.1	1.0	1.0	1.1
2000	2200							0.9	1.0	1.0	0.9	1.0	1.1
2400	2200							0.8	0.9	1.0	0.9	1.0	1.0


U-value door, U_d is based on narrow profile and given in W/m^2K . U-value for glass, U_g refers to centre point measurement and is given in W/m^2K . Glass, triple-glazed unit with warm edge, thickness 42 mm. Glazing bar width 74 mm. All values with insulated rebate door sill.

Typical sound reduction values. Sapa Door Systems	2086 SX Plus		
	Sound reduction values		
Typical sound values, fully glazed single door, size 1180x2130 mm.	R_w	R_w+C	R_w+C_{tr}
Glass T4-16-4-16-4. NSG Pilkington	34	33	29
Glass T6-16-4-16-8.8. NSG Pilkington	42	41	37
Glass TS 51/50. SGG Emmaboda Glass	44	43	38
	Sound reduction values		
Typical sound values, solid fill panel in single door, size 1180x2130 mm. *	37	35	31


* Solid infill panel, thickness 53 mm, construction from outside inwards:

- 1.5 mm aluminium sheet
- 5 mm wood fibre
- 40 mm closed cell plastic
- 5 mm wood fibre
- 1.5 mm aluminium sheet


Clear dimension, Sapa 2086



Rebate door



Door with anti-finger trap device, rubber seals



Door with concealed hinge

A= Free opening
B= Frame outer dimensions
C= Wall opening

Universal hinge:
D= 151 mm
with replaceable rebate


Butt hinge:
D= 145 mm
with replaceable rebate
D= 148 mm

Concealed hinge:
D = 98.5 mm
with replaceable rebate:
D = 101.5 mm

Integrated rebate:
E= 67 mm
Replaceable rebate sections
E= 70 mm


Glass, Sapa 2086

Glass thickness 20-64 mm




Glazing unit, symmetrically installed, Sapa 2086

Glass thickness 32-42 mm




Attachment alternatives, Sapa 2086



Single doors ≥ 1200 mm and double doors must be fixed at the top edge.
Door element must be attached to a suitable rigid wall structure.
The choice of fixing method depends on the wall type.

Infill panels, Sapa 2086

Infill panel F1
1.5 mm aluminium sheet
max. 60 mm
insulation 1.5 mm
aluminium sheet



Infill panel F2
1.5 mm aluminium sheet
4.8 mm board max. 50
mm insulation 4.8 mm
board 1.5 mm aluminium
sheet

Infill panel F3
1.5 mm aluminium sheet
max. 50 mm
insulation 10 mm
chipboard 1.5 mm
aluminium sheet


Read more in section
on Glazed Elements.

Fittings

Design the entire solution. Our system solutions offer many different possible combinations. A selection is shown below.



2086/2074/2050 narrow profile, outside.



2086/2074/2050 modular profile, outside.

Door handles and levers.



Semicircular handle with concealed attachments. Height 300 mm, Ø 30 mm. Aluminum or stainless steel.



Triangular handle with concealed attachments. Height 300 mm, Ø 30 mm. Aluminum.



Offset handle with concealed attachments. Height 300 mm, Ø 30 mm. Aluminum.



Lever handle for inner door
Lever handle, knob, rosette and cylinder rosette with modular profile. Width 137 mm, Ø 21 mm.



Universal hinge.



Lap butt hinge.



Concealed hinge.



sapa:

By  **Hydro**

Hydro Building Systems, region North

Sweden

SE-574 81 Vetlanda
T +46 (0)383 942 00
E sapa.se@hydro.com

Norway

NO-2027 Kjeller
T +47 63 89 21 00
E sapa.no@hydro.com

Denmark

DK-8240 Risskov
T +45 8616 0019
E sapa.dk@hydro.com

Finland

FI-02180 Espoo
T +358 (0)9 867 82 80
E system.fi@hydro.com

Lithuania/Estonia/Latvia

LT-02244 Vilnius
T +370 (0)5 210 25 87
E sapa.lt@hydro.com

Poland

92-620 Łódź, Polska
T +48 (0)42 683 63 73
E sapa.pl@hydro.com

sapabuildingsystem.com